

Pneumatic Wheel Lifter

34198000

Pneumatic Wheel Lifter

- For efficient, quick, and safe changing of wheels.
- Helps to comply with regulations regarding the working environment and safety in the workplace.

Features :

- Lifts wheels in less than 10 seconds and in one continuous movement.
- Stops precisely at the desired position
- Additional compressed air outlet to connect an air wrench
- Wheels rest on 2 rollers making it easy to turn the wheel until the correct position is found
- The rollers are displaced from the main pneumatic piston, giving free access to the wheel bolts
- Sturdy, lockable wheels make it easy to move the wheel lifter around the workshop

Benefits :

- Reduces risk of injury due to heavy lifting - enhances Health & Safety procedures
- One-man operation
- Ideal for lifting SUV/4WD/Van Wheels and Tyres

Specifications :

- Suitable for Wheel / Tyre overall diameters from 13" - 24" (325 - 600mm)
- Lifting capacity up to 65 kg
- Max. lifting height 830 mm
- Compressed air capacity 6-10 kg/cm²
- Width : 700 mm
- Height : 1880 mm



Wheel Handling Trolley

34199000

Wheel Handling Trolley

For mounting and dismounting large wheels on SUV's/4WD's/Vans/Trucks etc.

- Makes wheel handling operations safer, easier, and more convenient.
- Rotating rollers make it easy to turn the wheel until the correct position is found
- The rollers can be fitted in 3 positions for different wheel sizes

Specifications :

- Roller positions :
- Outer - 620mm / Middle - 450mm / Inner 290mm
- Length of rollers: 220 mm
- Lifting height: approx. 100 mm
- Max. weight of wheel: 150 kg
- Min. diameter of wheel: Ø600 mm
- Max. diameter of wheel: Ø1100 mm



Cordless Impact Wrench 19.2v 90802600

Features :

- Heavy Duty 600Nm Impact Wrench
- Achieves maximum torque of 600Nm (443 ft lbs) in 7 seconds
- Fan cooled motor with convenient forward / reverse switch
- Cushioned grip and light weight (only 2.8Kg / 6 lbs) for outstanding ergonomics
- Supplied in blow-moulded case, with TWO batteries and charging base
- Specification :
 - 1/2 square drive
 - maximum torque (reverse mode) - 600Nm (443 ft lbs)
 - Speed : 1800 RPM
 - Impacts : 2400 blows per minute
 - Battery : Sanyo 1.7Ah / 19.2v
 - Charge time : 60 minutes
 - Weight : 2.8 Kg (6 lbs)



Spare parts :-

- | | |
|----------|---------------------------|
| 908026BP | Replacement Battery Pack |
| 908026CB | Replacement Charging Base |

Hi-Torq Air Impact Wrench 1/2" sq dr - Composite Body

92420000

Features :

- Ultra High Performance Impact Hammer for extreme usage applications
- 900Nm / 660ft.lbs (1290Nm / 945 ft.lbs reverse)
- Composite Body Housing for reduced weight and increased stability
- 2.2kgs / 4.85lbs
- Twin-Line Double Hammer Impact - Fast Torque Build-Up
- Power control trigger system
- 4 Forward Control Steps - 1 Reverse

Specification :

- square drive
- 8000 rpm
- 184mm / 7.2" length
- Air Consumption - 113 l/min @ 6.2 bar (4.0 cfm @ 90psi)
- BSP inlet
- 900Nm / 660ft.lbs forward torque
- 1290Nm / 945 ft.lbs reverse torque
- Full Instructions included
- Spare Parts list included

